



Declaration of Performance

DOP No. 0432-CPR-00095-111



0432

1. Unique identification code of the product types:

**Rigid liners and connecting flue pipes made of stainless steel
for standard applications "System MKS OVAL" EN 1856-2: 2009**

2. Identification of the construction product, in accordance with Article 11 § 4:

System MKS OVAL

Version 1	T450 – N1 – D – V2	– L50060 – G NM – L50080 – G NM – L50100 – G NM
Version 2	T450 – N1 – W – V2	– L50060 – O NM – L50080 – O NM – L50100 – O NM
Version 3	T450 – N1 – D – V3	– L50060 – G NM – L50080 – G NM – L50100 – G NM
Version 4	T450 – N1 – D – V2	– L50050 – G NM
Version 5	T450 – N1 – W – V2	– L50050 – O NM
Version 6	T450 – N1 – D – V2	– L99050 – G NM – L99060 – G NM – L99080 – G NM – L99100 – G NM
Version 7	T450 – N1 – W – V2	– L99050 – O NM – L99060 – O NM – L99080 – O NM – L99100 – O NM
Version 8	T450 – N1 – D – Vm	– L20050 – G NM – L20060 – G NM – L20080 – G NM – L20100 – G NM
Version 9	T450 – N1 – W – Vm	– L20050 – O NM – L20060 – O NM – L20080 – O NM – L20100 – O NM

NM – not measured value means 3 x nominal diameter at least 375 mm

3. Use or intended use of the construction product in accordance with the relevant harmonized technical specification as provided by the manufacturer:

Evacuation of combustion products from the furnace to the outside atmosphere for standard applications (negative pressure), for gaseous fuels, heating oil and solid fuels (dry)

4. Name, company name or trademark and contact address of the manufacturer, in accordance with Article 11 § 5:

MK Sp. z o.o.

ul. Wiśniowa 24

PL 68-200 Żary

Tel: +48684581919; Fax: +48684581914

e-mail: sekretariat@mkzary.pl

5. Name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12 §2:

not applicable

6. The system or systems of assessment and verification of constancy of performance of construction product in accordance with Annex V:

System 2+ and System 4

7. Notified body certifying the factory production control **No 0432**



has carried the initial inspection of the factory and control of factory production and performs the continuous surveillance, assessment and approval of factory production control and on the 15.07.2015 has issued the compliance certificate **Nr 0432-CPR-00095-111** for the factory production control.

8. **Declared performance in accordance with EN 1856-2:2009, annex ZA**


Essential characteristics	Performance	Comments
Materials and sheet thicknesses		
Exhaust pipe	DN oval from (110x140) to (130x240) Version 1, 2 and 3 0,6 mm (minimum 0,54 mm) 0,8 mm (minimum 0,72 mm) 1,0 mm (minimum 0,90 mm) Version 4 and 5, 1.4404; 1.4571 0,5 mm (minimum 0,45 mm) Version 6 and 7 1.4521 0,5 mm (minimum 0,45 mm) 0,6 mm (minimum 0,54 mm) 0,8 mm (minimum 0,72 mm) 1,0 mm (minimum 0,90 mm) Version 8 and 9 1.4301 0,5 mm (minimum 0,45 mm) 0,6 mm (minimum 0,54 mm) 0,8 mm (minimum 0,72 mm) 1,0 mm (minimum 0,90 mm)	
Thermal insulation	Version 3 30 mm pipe section insulation (density: minimum 105 kg/m ³)	
Mechanical strength		
Compressive strength Segments of the chimney, fittings and supports	Version 1 - 9 to 20 m	For more information, see the manual
Non-vertical installation	Version 1 - 9 3 m at 45°	The maximum distance between two supports
Working conditions		
Fire resistance	Version 1, 3, 4, 6, 8: YES to T450 – G NM 3 x DN , at least 375 mm Version 2, 5, 7, 9: NOT to T450 – O NM 3 x DN , at least 375 mm	NM – not measured
Tightness	N1	Working in negative pressure
Flow resistance Fittings and terminals; Roughness	According to EN 13384-1, R = 1 mm	Normative value: see the method of calculation

Thermal resistance	Version 3 0,56 m ² K/W	Specified at 200 °C
Resistance to thermal shock		
Heat load at nominal temperature	T450	Test temperature 550°C
Sootfire resistance	Version 1, 3, 4, 6, 8: YES (designation G)	Tested at 1000°C (30 min.)
	Version 2, 5, 7, 9: NOT (designation O)	Test temperature 550°C
Durability		
Water vapor diffusion and water resistance	Version 2, 5, 7, 9 YES	
Condensate penetration resistance	Version 2, 5, 7, 9 YES	
Corrosion resistance	Version 3: V3	For gas, fuel oil and solid fuels (dry running)
	Version 1, 2, 4, 5, 6, 7: V2	For gas, fuel oil and wood (open furnace)
	Version 8, 9: Vm	For gas
Freeze-thaw resistance	YES	
Additional information		
Carrying away of condensate	(D) M251 instruction of Sewage Disposal Methods Association	Necessary neutralization of sewage
Storage conditions	Do not store in corrosive environment	
Methods of cleaning	Do not use the tools of black steel	
Position of cleaning openings	(D): According to DIN 18 160	Observe the national regulations
Identification of flue systems	(D): According to DIN 18 160 Durable plate, mounted on installation, housing or casing	Observe the national regulations
Protection against contact	Labeling or spacers at temperatures ≥ 70 °C	EN 1856-1
Direction of flow	Core pipe female socket upwards	
Installation and assembly	Follow the instructions	

9. The performance of the product identified in points 1 and 2 is consistent with the declared performance in point 8.
This declaration of performance is issued under the sole responsibility of the manufacturer mentioned in point 4.

On behalf of the manufacturer signed:


.....
Kinga Pachnik – Managing Director


.....
Ireneusz Koman – Plant Director

Żary 01-09-2015